

## CARRELLO ELEVATORE STILL R 60-45

### ELETTRICO GOMME ANTITRACCIA

#### DIMENSIONI:

H: 2,75 mt.

Largh.: 2,20 mt.

Lungh.: 2,85 mt.

Mis. forche: lunghezza 220 cm x 15 cm x 5 cm

#### CAPACITA' DI SOLLEVAMENTO:

fino a 4 Ton.



|       |                          |          |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|-------|--------------------------|----------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| XE 45 | Altezza sollevamento     | $h_3$ mm | 3000 | 3300 | 3600 | 3800 | 4000 | 4200 | 4500 | 4700 | 5000 | 2950 | 3050 | 3250 | 3450 | 3650 | 3850 | 4050 | 4350 | 4650 | 4950 | 5400 | 5700 | 6000 | 6450 | 6750 | 7050 | 7350 |
|       | Altezza minimo ingombro  | $h_1$ mm | 2200 | 2350 | 2500 | 2600 | 2700 | 2800 | 2950 | 3050 | 3200 | 2200 | 2250 | 2350 | 2450 | 2550 | 2650 | 2750 | 2300 | 2400 | 2500 | 2650 | 2750 | 2850 | 3000 | 3100 | 3200 | 3300 |
|       | Altezza massimo ingombro | $h_4$ mm | 3870 | 4170 | 4470 | 4670 | 4870 | 5070 | 5370 | 5570 | 5870 | 3800 | 3900 | 4100 | 4300 | 4500 | 4700 | 4900 | 5400 | 5700 | 6000 | 6450 | 6750 | 7050 | 7500 | 7800 | 8100 | 8400 |
|       | Alzata libera            | $h_2$ mm | 80   | 80   | 80   | 80   | 80   | 80   | 80   | 80   | 80   | 1350 | 1400 | 1500 | 1600 | 1700 | 1800 | 1900 | 1350 | 1450 | 1550 | 1700 | 1800 | 1900 | 2050 | 2150 | 2250 | 2350 |